

## APC EASY UPS BV 650VA, AVR, IEC Outlet, 230V

### BV650I

Call for More Information



- Easy UPS provides power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
- Includes: User Manual

#### Output

Output power capacity	375Watts / 650VA
Max Configurable Power (Watts)	375Watts / 650VA
Nominal Output Voltage	230V
Output Frequency (not synced)	50/60 Hz +/-1 Hz
Topology	Line Interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(6) IEC 320 C13 (Battery Backup)
Transfer Time	6ms typical : 10ms maximum

#### Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	IEC-320 C14
Cord Length	1.5meters
Input voltage range for main operations	170 - 280V
Number of Power Cords	1

#### Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	8hour(s)
Expected Battery Life (years)	3 - 5
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC EASY UPS BV 650VA, AVR, IEC Outlet, 230V | BV650I | Downloaded on 06/28/2020 (EST)

### Communications & Management

Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

### Surge Protection and Filtering

Surge energy rating	156Joules
---------------------	-----------

### Physical

Maximum Height	92MM, 9.25CM
Maximum Width	160MM, 16.05CM
Maximum Depth	305MM, 30.5CM
Net Weight	4.5KG
Shipping weight	4.8KG
Shipping Height	237MM, 23.7CM
Shipping Width	143MM, 14.3CM
Shipping Depth	373MM, 37.3CM
Color	Black
SCC Codes	1073130433830 4

### Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 90 %
Operating Elevation	0-2000.1meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 90 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	40.0dBA
Protection Class	IP 20

### Conformance

Approvals	EN/IEC 62040-1, EN/IEC 62040-2
-----------	--------------------------------

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC EASY UPS BV 650VA, AVR, IEC Outlet, 230V | BV650I | Downloaded on 06/28/2020 (EST)

Conformance	
Standard warranty	2 years repair or replace

  

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains SVHCs

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.