



Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

General

Provided equipment	Basic UPS signalling RS-232 cable CD with software Country-specific detachable power cord 1 x DC cable User manual USB cable
Number of tare power	40 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Cable length	1.52 m
Colour	Black
Depth	42.5 cm
Height	33.6 cm
Net weight	45.9 kg
USB compatible	Yes
Width	42.5 cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	100...280 V adjustable (half load)
Inputvolt_other	220 V 240 V
Number of cables	1
Input voltage	230 V

Output

Rated power in W	2400 W
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	6 IEC 60320 C13 1 IEC 60320 C19
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve fixed loss	0.0229
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0.0382
Curve square loss	0.0289
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	88 % (full load)
Graph display	1
Half load runtime	00:13:00 1200 W
Output voltage	230 V
Maximum configurable power in VA	3000 VA
Rated power in VA	3000 VA
Runtime at 600W	00:31:00
Transfer time	4 ms typical

Conformance

Product certifications	CE EAC
Standards	IEC 62040-1-1 IEC 62040-1-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...15000 m
Acoustic level	50 dB
Show note OP temperature	No
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	D
Battery power in VAH	939 VAh runtime
Battery option	SRV72BP-9A 1 1878 VAh SRV72BP-9A 2 2817 VAh SRV72BP-9A 3 3756 VAh SRV72BP-9A 4 4695 VAh

Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	49.8 kg
Package 1 Height	46.5 cm
Package 1 width	56.5 cm
Package 1 Length	56.5 cm

Offer Sustainability

RECh Regulation	REACH Declaration
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------