



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Basic UPS signalling RS-232 cable CD with software User manual USB cable
--------------------	---

Physical

Colour	Black
Depth	37.4 cm
Height	68.5 cm
Net weight	54 kg
Width	19 cm

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Input voltage limits	110...300 V adjustable (half load) 176...300 V
Inputvolt_other	220 V 240 V
Input voltage	230 V

Output

Rated power in W	6000 W
Maximum configurable power in W	6000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V

	240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Output connector type	Hard wire 3-wire (H N + E) 1
Bypass type	Internal bypass (automatic and manual)
Output voltage	230 V

Conformance

Product certifications	CE
Standards	IEC 62040-1-1 IEC 62040-1-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...60 °C
Storage altitude	0.00...15240.00 m
Acoustic level	55 dB
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Liquid value	0

Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	66 kg
Package 1 Height	91 cm
Package 1 width	29 cm
Package 1 Length	49.5 cm

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------